

---

# **LiDAR.jl Documentation**

***Release 0.0.1-rc1***

**Jiayan Chen and Huckleberry Febbo**

**Aug 23, 2017**



---

## Contents

---

<b>1 Table of Contents</b>	<b>3</b>
1.1 Installation on Ubuntu 16.04 . . . . .	3
1.2 Basic Usage . . . . .	5



This is software for LiDAR model that is used to help navigate an a model of an autonomous ground vehicle.



# CHAPTER 1

---

## Table of Contents

---

### Installation on Ubuntu 16.04

#### 1. julia programs needed

get and build:

```
Pkg.add("RobotOS")
Pkg.add("PyCall")
Pkg.build("RobotOS")
Pkg.build("PyCall")
```

#### 2. Gazebo

Install:

```
curl -ssL http://get.gazebosim.org | sh
```

Run:

```
gazebo
```

More information is [here](#)

#### 3. ROS

Follow the instructions [here](#)

Note: In step # 1.4, run this one (the full one seems to be broken):

```
sudo apt-get install ros-kinetic-desktop
```

## 4. Initialization of Package

### 4.1. Run `cmake .` and `make`

1. open another terminal -> `ctr``+``shift``+``t`
2. navigate to the folder `.scr/c_code`
3. in the terminal type `cmake .` and hit enter
4. in the terminal type `make` and hit enter

### 4.2. Set path for gazebo plugins

Not sure if this needs to be done:

A. in the terminal type (only should have to do during initialization):

```
export GAZEBO_PLUGIN_PATH=$HOME/gazebo_plugin_tutorial/build:$GAZEBO_PLUGIN_PATH  
TODO: need to change path
```

### 4.3 Get the `velodyne_hd132` model for Gazebo

Either:

1. Fork the `gazebo_models` database by visiting [https://bitbucket.org/osrf/gazebo\\_models/fork](https://bitbucket.org/osrf/gazebo_models/fork).

**OR**

2. Just copy the folder `./LiDAR/scr/gazebo/gazebo_models` into `$HOME/gazebo/models/`

#### Note

press `ctr + h` to show hidden folders (..like `.gazebo`)

## Potential Issues

### 1. running using RobotOS in julia -> fails

This may be due to path issues was fixed [here](#).

- Additional info [here](#)
- NOTE: the following is designed for use with Ubuntu 16.04

## Basic Usage

### 1. Start roscore

#### Background Information

**roscore** is a collection of nodes and programs that are needed to use a ROS system.

- A roscore must be running for ROS nodes to talk

#### Linking GAZEBO to ROS

- GAZEBO can be linked to ROS using [this link](#).

#### Linking ROS to julia

- ROS can be linked to julia using [this package](#).

1. open a new terminal -> `ctrl``+``alt``+``t`

2. in the terminal type `roscore` and hit enter

### 2. Make a ROS node in python that communicates to a julia node

1. open another terminal -> `ctrl``+``shift``+``t`

2. navigate to the folder containing `echoinode.py` (i.e. `./scr`)

3. in the terminal type `python echonode.py` and hit enter

### 3. Run a julia function that can communicate with the LiDAR model

1. open another terminal -> `ctrl``+``shift``+``t`

2. navigate to the folder containing `handler.jl` (i.e. `./scr`)

3. in the terminal type `julia` and hit enter

#. in the `julia` type:

```
include("handler.jl")
```

### 4. run gazebo model of the LiDAR

1. navigate to the folder `.scr/c_code`

2. in the terminal type `gazebo velodyne.world` and hit enter

- A Gazebo gui should appear on the screen